



Plumbing Pre-Installation Recommendations

- 100 gallon dedicated hot water tank or tankless hot water heater with 3/4" lines rated for a minimum of 18 gpm.
 - 3/4" plumbing lines with 3/4" mixing valves to be used with included rapid fill fittings or installer supplied faucet.
- Recommended minimum flow rate is 18 gpm.

Patents recieved or pending.

Note: Dimensional Tolerances: ±1/4"

Drop-in-Hole Size:
 Operating Capacity:
 Overflow Capacity:
 Floor Loading / sq.ft.:
 Cartoned Wt:
 Cube:

HSC650
 76" Diameter
 91 / 170 gal
 200 gal
 70.9 lbs
 360 lbs
 115 cu. ft.

Construction: Fiberglass reinforced acrylic bath with Level Form™ full-support base

We provide products listed with Intertek ETL and International Association of Plumbing and Mechanical Officials (IAPMO). Consult factory with your listing requirements.

Signature

SIGNATURE EDITION: 240 V System. Two quiet, 1 1/2 HP, 3-speed pumps, each with heater; 1HP, variable speed air blower with integral air heater; Two front access LED mood lights for synchronized chromotherapy; Two digital controls with LCD display windows, low water level and water temperature sensors, 20-minute timer and automatic air channel purge cycle; Two controllers operate 3-speed pumps, air blower speed and mode (continuous, wave or pulse) and shows water temperature and time remaining.

Home Spa also includes a Sound Immersion System, an aromatherapy dispensing system with two back massage therapy zones each with jetted neck pillow, and an automatic Ozone System. Also included is a floating universal remote control that controls all functions of both whirlpool pumps, air blower, air heater, LED mood lights, jetted neck pillows, and Sound Immersion Transducers that can also be used with your TV, DVD, or CD, etc.